



Active Mobility

# LIFTING HOISTS

Ceiling Hoists  
Gantry Systems  
Tracking Systems  
Ceiling Hoist Accessories

Intelligent Mobility Solutions



# FOLDING HOISTS

## Birdie EVO Compact 150



The **Birdie EVO Compact 150** mobile lifting hoist is of a smaller footprint for easier maneuverability, which has been designed with new technologies to ensure maximum comfort and security, when lifting or transferring a patient to or from a bed, chair or the floor.

This range has been based on the renowned Birdie. The Birdie EVO Compact includes an ergonomic lift, which allows the client to be easily rotated 360 degrees, making positioning easier for the carer and reducing difficulty for the patient.

It offers maximised space, the high boom ensures there is space for the client, even when the hoist is in its highest position. The optimised space in front of the actuator reduces the risk of injury to the client's knees.

The Birdie EVO Compact can be easily folded and unfolded without the need of tools. This ensures it takes up minimal space when stored and makes it easy to push and transport.

## Oxford Advance



The **Oxford Advance** Patient Lift has an oversized handle for increased control as well as a compact design. It has a patent pending push footpad that reduces the force needed to initiate the movement.

The swan neck leg design accommodates large furniture and it's patent pending triangular folded design allows the lift to securely stand unaided. Furthermore no tools are needed to fold the aluminium construction and the foot operated leg spreading mechanism requires no bending to operate.

Specifications			
Birdie EVO 150		Oxford Advance	
Safe Working Load	150kg	Safe Working Load	150kg
Length	1090mm	Maximum Overall Length	1300mm
Minimum Base Width	520mm	Minimum Overall Length	1250mm
Maximum Base Width	845mm	Maximum Overall Height	1860mm
Arm Height	525-1615mm	Minimum Overall Height	1360mm
Ground clearance	100mm	Overall Weight: Approximately	29kg
Unit weight	36kg	Width	550mm
Battery time	40 cycles	Maximum Height Spreader Bar	1690mm
		Minimum Height Spreader Bar	390mm
		Overall Height of Legs	115mm
		Ground Clearance	30mm

# FOLDING HOISTS

## Carina 350



**Carina 350** has a relatively narrow and compact design, which means that the lift can fit into and reach practically anywhere, even in tight spaces. In spite of the handy size, Carina 350 offers a very large lifting range and, therefore, Carina350 can manage most lifting situations and requirements; both low and high lifting, seated or supine, to and from the floor, bed or chair. Carina350 is a foldable, mobile patient lift adapted for safe and easy lifting of users weighing up to 165 kg/350 lbs. Carina350 is available in four variants, with manual or electrical base widening and with standard height or low legs. All variants are sturdy, stable and safe and, at the same time, light-weight for steel lifts.

## Molift Smart 150



**The Molift Smart 150** is a lightweight, portable patient lifter designed to be easily wheeled and transported. It is ideally suited for use in home care, for travelling, transporting in a car or to be easily stored. With a lifting range of 27 – 168 cm the Smart 150 provides an excellent maximum lifting height and at the same time gets low enough to facilitate lifting from the floor.

The 4-point sling suspension is standard and guarantees the patient hoist gives a comfortable lifting position for the user with ample space around the head area thereby eliminating any risk of the head bumping into the suspension or the user swinging side to side.

With the combination of sling and suspension, the user will slide into a natural, correct seating position, from lying to sitting and vice versa.

The Smart 150 has a unique design with an excellent centre of balance and together with the small footprint makes it easy to manoeuvre even in tight spaces.

Specifications		Carina 350		Molift 150	
Safe Working Load		165kg		150kg	
Material		Powder-coated steel		26kg (can be separated into 2x13 parts)	
Total height		1290-1840mm		1200mm	
Base Height		1150mm		660mm	
Base width (outer dimensions)		680-1080mm		925mm	
Base width (inner dimensions)		560-940mm		110mm	
Base widening		Manual or Electrical		NiMH 14.4V - 2.2Ah	
Total weight		Man.: 34.5kg, Elect.: 36kg		3 hours	
Front castors (diameter)		100mm (low legs: 35mm)		270-1665mm	
Rear Castors (diameter)		100mm		6cm/sec	
Lifting range		580-1680mm		1410mm	
Lifting speed without load		23mm/sec		Rated performance	40 hoists at 75kg and 500mm
Emergency lowering		Manual and Electrical		Service software Included	
Battery capacity		2.9Ah		Material	Aluminium, steel
Sling bar material		Aluminium			
Sling bar Width		450mm			
Protection class		IPX4			

# FOLDING HOISTS

## Neos 150



The folding, aluminium **Neos** lifting hoist has a SWL of 150kg while its quick-release folding structure allows the hoist to be folded for storage and transfers.

Both lifting and raising functions are powered by Linak with an average lifting range of 1240mm while leg adjustment done through a foot pedal control to a maximum internal width of 890mm.

Stocked with safety features such as easy access to emergency lowering devices and an anti-entrapment feature which stops the boom from lowering any further when it encounters resistance.



### Specifications

### Neos

Safe Working Load	150kg
Base Length	1290mm
External Base Width Closed	615mm
External Base Width Open	965mm
Internal Base Width Closed	550mm
Internal Base Width Open	890mm
Base Width Adjustment	Manual
Under Bed Clearance	135mm
Minimum Height Yoke	410mm
Maximum Height Yoke	1650mm
Average Lift Range (with GP Large Sling)	1240mm
Lifter Weight	35kg
Minimum Storage Height	1370mm
Under Base Height	72mm
Maximum Hoist Reach	880mm
Minimum Hoist Reach	440mm
Hoist Reach at Maximum Height	450mm



## Sonata 150 - Manual Spread Leg



**Sonata 150** is a lightweight compact mobile patient lifting hoist with a safe working load (SWL) of 150kg and an innovative and ergonomic design. The Sonata 150 is an easy to use everyday lifter providing superior patient lift space through the use of SPACE LINK Technology.

### SPACE LINK Technology

The SPACE LINK Technology is a breakthrough for optimising patient space as it increases the maximum lifting height of the hoist. It also enhances floor lift capability and is compatible with both standard spreader bar and pivot frames.

Lightweight, compact mobile patient lifting hoist  
Innovative and ergonomic design  
Utilises SPACE LINK Technology for superior patient lifting space



## Sonata 150 - Electric Spread Leg



A lightweight compact mobile patient lifting hoist with innovative and ergonomic design. **The Sonata ELS** is an easy to use everyday lifter. With a safe working load of 150kg the Sonata ELS offers an outstanding lift capacity in a small patient hoist.

The Sonata ELS offers all the versatility of the original Sonata, with the added advantage of Electric Leg Spread. This allows for easy of lifter leg adjustment on carpeted surfaces and/or with the heavier client on board.

Featuring Linak Jumbo Care advanced diagnostic control system  
Powered by LA44 European Standards compatible linear actuator



Specifications			
		Manual Spread Leg	Electric Spread Leg
Safe Working Load	150kg	Safe Working Load	150kg
Base Length	1005mm	Base Length	1100mm
External Base Width Closed	605mm	External Base Width Closed	670mm
External Base Width Open	1070mm	External Base Width Open	1075mm
Internal Base Width Closed	510mm	Internal Base Width Closed	570mm
Internal Base Width Open	975mm	Internal Base Width Open	970mm
Base Width Adjustment	3 Position Manual	Base Width Adjustment	Electric
Under Bed Clearance	130mm	Under Bed Clearance	130mm
Minimum Height Yoke	420mm	Minimum Height Yoke	400mm
Maximum Height Yoke	1735mm	Maximum Height Yoke	1735mm
Average Lift Range (with GP Large Sling)	870mm	Average Lift Range (with GP Large Sling)	880mm
Lifter Weight	41kg	Lifter Weight	41kg
Minimum Storage Height	1260mm	Minimum Storage Height	1250mm
Under Base Height	55mm	Under Base Height	55mm
Maximum Hoist Reach	875mm	Maximum Hoist Reach	865mm
Minimum Hoist Reach	555mm	Minimum Hoist Reach	515mm
Hoist Reach at Maximum Height	555mm	Hoist Reach at Maximum Height	515mm
Mass of Heaviest Part	22kg (Mast assembly)	Mass of Heaviest Part	21kg (Mast assembly)

# STANDARD HOISTS

## Micros 130



**Micros 130** Compact aluminium lift with a Safe Working Load of 130kg with electric raise and lower powered by Linak. The Micros 130 offers foot pedal control for leg adjustment and a quick release yoke. The Micros 130 is equipped with 100mm front castors and 125mm locking rear castors.

Quick release structure enables quicker more compact disassembling. Micros 130 is stocked with safety features such as the Jumbo Care diagnostic control and service monitor system that allows you to monitor the hoist and ensure that you're up-to-date with its servicing. Available with yoke or pivot attachment.



## Solar 175



**Solar's** Scandinavian design with its sweeping elegant lines makes an attractive choice for home care or institutional use. Its excellent lifting range allows clients to be lifted from the floor.

The design and shape of the chassis provides the client with a maximum of space for a more relaxed transfer. The curved legs allow a wider base spread to access large chairs or wheelchairs. Ergolet's patented spreader bars always ensures safe and simple sling attachment.

Solar uses the most advanced Linak control box, which includes an LCD display that shows current action and service information.

The system records and shows the number of lifts performed and also the date of the next service.

Specifications	Micros 130
Safe Working Load	150kg
Base Length	1100mm
External Base Width Closed	670mm
External Base Width Open	1075mm
Internal Base Width Closed	570mm
Internal Base Width Open	970mm
Base Width Adjustment	Electric
Under Bed Clearance	130mm
Minimum Height Yoke	400mm
Maximum Height Yoke	1735mm
Average Lift Range (with GP Large Sling)	880mm
Lifter Weight	41kg
Minimum Storage Height	1250mm
Under Base Height	55mm
Maximum Hoist Reach	865mm
Minimum Hoist Reach	515mm
Hoist Reach at Maximum Height	515mm

	Solar 175
Safe Working Load	175kg
Number of lift movements	40-60 with 80kg / 0.5m lift
Weight	50kg
Lifting interval	636-1970mm
Width	min-680mm
Emergency lowering	Manual or electronic
Battery capacity	2.9Ah
Material	Powder coated steel
Turning diameter	1430mm
Hoisting range	1342mm
Max. internal width	920mm
Internal width at max. reach	893mm
Min. internal width	550mm



## Oxford Midi 180



Offering the perfect solution for both community and nursing environments whilst being sympathetic to space constraints the **Oxford Midi 180** has become the 'gold standard' in homecare.

This excellent, high quality hoist features an excellent emergency lift - this is a spring loaded mechanical lowering device that will only operate under load.

The Oxford Midi 180 Electric Hoist has an angled boom to assist with lifting from the floor, and a large push handle that helps the hoist to be manoeuvred with ease. The hand held controller promotes independent patient use so the carer has both hands free to provide support. The spreader bar is also padded for additional patient safety.

## Birdie EVO 180



The new has been designed to offer a high feature-set of options that have been blended with new technologies to provide maximum comfort and security when lifting or transferring a patient to or from a bed, chair or even the floor.

Based on the renowned Birdie, the new range has been customer insight led, encompassing everything that was valued on the Birdie whilst bringing in new features to further enhance the client and carer experience.

The BirdieEVO encompasses an ergonomic lift that allows the client to be easily rotated 360°, making positioning much easier for the carer and reducing anxiety for the client.

The high boom ensures there is space for the client, even when the hoist is in its highest position, and the optimised space in front of the actuator reduces the risk of injury to the client's knees.

Specifications	Oxford Midi 180		Birdie EVO 180
Safe Working Load	180kg	Safe Working Load	180kg
Length	1225mm	Length	1220mm
Min Overall Height	1240mm	Min. base width	640mm
Max Overall Height	1840mm	Inside base width	1020mm
Min Spreader Bar Height	525mm	Lifting range	415-1660mm
Max Spreader Bar Height	1660mm	Ground clearance	35mm
Spreader Bar Reach at Min Height	440mm	Weight	40kg
Spreader Bar Reach at Max Height	420mm	Battery time	40 cycles
Spreader Bar Height at Max Reach	1060mm		
Max Reach	656mm		
Turning Radius	1235mm		
Legs Open - External Width	1170mm		
Legs Open - Internal Width	1070mm		
Legs Closed - External Width	600mm		
Legs Closed - Internal Width	540mm		
Overall Height of Legs	100mm		
Ground Clearance	25mm		
Front Twin Castors	75mm		
Rear Braked Castors	100mm		
Total Weight	42kg		

# STANDARD HOISTS

## Eva 400



**Eva 400** is a versatile mobile patient lift for all lifting situations and for users weighing up to 180 kg/400 lbs. When used with Handicare's functional and easy-to-use SystemRoMedic™ lifting accessories, Eva400 is the right choice for lifting in connection with transfers to and from the floor, chair or bed, as well as for horizontal lifting and gait training.

### Two variants with different base-width adjustment

Eva400 is available in two variants; with electrical (EE) or manual (EM) base-width adjustment. Both variants of Eva400 are supplied complete and ready to use, fitted with a stable sling bar with reliable safety latches and a hand control. The sling bar is standard width (450 mm/17.7") which is suitable for most users and lifting situations.

Specifications	Eva 400 Electric Leg spread
----------------	-----------------------------

Safe Working Load	180kg
Material	Aluminium
Base width (outer dimensions)	685-980mm
Base width (inner dimensions)	585-880mm
Base widening	Electrical
Total weight	34kg
Castors (diameter)	100mm
Lifting range	530-1790mm
Lifting speed without load	23mm/sec
Emergency lowering	Manual and electrical
Battery capacity	2.9Ah
Sling bar material	Aluminium
Sling bar width	450mm
Protection class	IPX4

Eva 400 Manual Leg spread
---------------------------

Safe Working Load	180kg
Material	Electrical
Base width (outer dimensions)	685-980mm
Base width (inner dimensions)	585-880mm
Base widening	Manual
Total weight	34kg
Castors (diameter)	100mm
Lifting range	530-1790mm
Lifting speed without load	23mm/sec
Emergency lowering	Manual and electrical
Battery capacity	2.9Ah
Sling bar material	Aluminium
Sling bar width	450mm
Protection class	IPX4



## Alto 200 Bariatric Hoist



A medium sized heavy duty mobile patient lifting hoist with a safe working load of 200kg and a compact ergonomic design. **Alto Lift 200**, whilst being compact, provides superior patient lift space through the use of SPACE LINK technology.

The Alto Lift 200 is the lifter of choice for institutional use or home care where a high capacity lift is required. Safe working load of 200kg and a innovative and ergonomic design.

- Increased maximum lifting height
- A breakthrough for optimised patient space
- Enhanced floor lift capability
- Compatible with standard spreader bar or tilt /pivot frame



## Forte 320 Bariatric Hoist



With a safe working load of 320kg this extremely heavy duty mobile patient lifting hoist provides full bariatric capability whilst remaining a compact and ergonomic design. Manoeuvrability and exceptional under bed clearance are key design features.

**The Forte 320** provides superior patient lift space through the combination of the recessed actuator and the use of SPACE LINK technology. The aesthetic design of the concealed electric leg mechanism provides infection control advantages.

***The Forte 320 is the ideal hoist for institutional use where a high capacity bariatric lifter is required.***



Specifications	Alto 200	Forte 320	100mm Front castors	Twin 75mm Castors
Safe Working Load	200kg	Safe Working Load	320kg	320kg
Base Length	1150mm	Base Length	1433mm	1420mm
External Base Width Closed	700mm	External Base Width Closed	715mm	715mm
External Base Width Open	1130mm	External Base Width Open	1205mm	1200mm
Internal Base Width Closed	600mm	Internal Base Width Closed	590mm	600mm
Internal Base Width Open	1030mm	Internal Base Width Open	1080mm	1080mm
Base Width Adjustment	Electric	Base Width Adjustment	Electric	Electric
Under Bed Clearance	130mm	Under Bed Clearance	126mm	111mm
Minimum Height Yoke	390mm	Minimum Yoke Height	260mm	245mm
Maximum Height Yoke	1830mm	Maximum Yoke Height	1955mm	1940mm
Average Lift Range (with GP Large Sling)	970mm	Overall Height (Boom Raised)	2248mm	2243mm
Lifter Weight	46kg	Lifter Weight	63.5kg	63kg
Minimum Storage Height	1350mm	Minimum Storage Height	1460mm	1445mm
Under Base Height	55mm	Under Base Height	31mm	15mm
Maximum Hoist Reach	875mm	Maximum Hoist Reach	810mm	810mm
Minimum Hoist Reach	450mm	Mass of Heaviest Part (Chassis)	37kg	37kg
Hoist Reach at Maximum Height	515mm			
Mass of Heaviest Part	24kg (Mast assembly)			

Oxford Presence



**The Oxford Presence** Lifter is a mobile, aluminium lifter that has an ergonomic foot pad that assists caregiver with initiating movement. There is a hand control clip that holds the pendant in place when not in use so as to prevent it from falling and being damaged. Its powered base allows caregivers to open and close it with a touch of a button, no need for bending or twisting, and its tapered leg design allows the disabled lifting hoist to be positioned closer to bulky objects such as commodes, wheelchairs and large chairs during transfers. Additionally its sculptured base design allows caregivers to get closer to clients during transfers, while concealing all working components. The Oxford Presence offers versatility in its range of sling systems.

Oxford Stature



**The Oxford Stature** is a mobile, powered hoist with a large lifting range that can be used to lift a person to and from a bed, chair or the floor. It has an interchangeable six point spreader bar or four point tilting frame for sling attachment. Suitable for domestic or healthcare facility use. With an extensive lifting range, the Stature copes easily with even the most demanding of patient handling situations. Careful attention to product design ensures correct ergonomic usage, protecting both the patient and caregiver from injury.

Specifications	Oxford Presence
Safe Working Load	227kg
Weight Overall	40kg
Length of Base	1460mm
Width Overall of Base Closed	670mm
Width Internal of Open Base	1020mm
Height of Base	120mm
Height of Spreader Bar	430-1910mm
Width of Base	665mm (external with legs closed)

	Oxford Stature
Safe Working Load	227kg
Weight Overall	73.5kg
Length of Base	1390mm
Width Overall of Base Closed	1050mm
Width Internal of Open Base	1230mm
Height of Base	110mm
Height of Spreader Bar	390-1550mm
Width of Base	760mm



## EvaDrive



**EvaDrive** is a new motorised lift which drastically reduces the force required for transfer and lifting of patients. Operating EvaDrive requires minimal strength and effort even in the narrowest of spaces. The intuitive control handle makes steering as simple as manoeuvring a shopping trolley. EvaDrive is operated intuitively with very little force. The control handle responds to gentle fingertip movements and is sufficiently precise to easily manoeuvre EvaDrive in very narrow spaces, for instance when repositioning patients in small hospital rooms. A gentle touch of the control handle and EvaDrive turns, reverses and moves forward with minimal effort. EvaDrive understands where you want to go – and takes you there. A single carer can easily operate the lift even with plus-size patients.

## Eva450



**Eva450** is a versatile mobile patient lift for all lifting situations and for users weighing up to 205 kg/450 lbs. Eva450 is the right choice for lifting in connection with transfers to and from the floor, chair or bed, as well as for horizontal lifting and gait training.

Eva450 is available with standard height legs or in a special low leg version for use with low height beds.

All variants of Eva450 are supplied complete and ready to use, fitted with a stable sling bar with reliable safety latches and a hand control. The sling bar is standard width (450 mm/17.7") which is suitable for most users and lifting situations.

Specifications	EvaDrive 205kg	EvaDrive 270kg	Eva450	
Safe Working Load	205kg	270kg	Safe Working Load	205kg
Material	Aluminium/Steel	Aluminium/Steel	Material	Aluminium
Base width, outer dimensions	685-980mm	750-1150mm	Base width, outer dimensions	685-980mm
Base width, inner dimensions	585-880mm	650-1050mm	Base width, inner dimensions	585-880mm
Total weight	58kg	64kg	Base widening	Electrical
Front castors, diameter	100mm	100mm	Total weight	34kg
Rear castors, diameter	200mm	203mm	Front castors, diameter	35mm (Low leg) or 100mm (standard height)
Lifting speed without load	35mm/sec	35mm/sec	Rear castors, diameter	100mm
Driving speed	7km/h	7km/h	Lifting range	500-1790mm
Emergency lowering	Manual	Manual	Lifting speed without load	35mm/sec
Battery	24V, 17.3Ah Li-Ion	24V, 17.3Ah Li-Ion	Emergency lowering	Manual and electrical
Sling bar width	450mm	600mm	Battery capacity	2.9Ah
Protection glass	IPX4	IPX4	Material, sling bar	Aluminium
			Sling bar width	450mm

# BARIATRIC HOISTS

## Eva 600



**The Oxford Presence** Lifter is a mobile, aluminium lifter that has an ergonomic foot pad that assists caregiver with initiating movement. There is a hand control clip that holds the pendant in place when not in use so as to prevent it from falling and being damaged.

Its powered base allows caregivers to open and close it with a touch of a button, no need for bending or twisting, and its tapered leg design allows the disabled lifting hoist to be positioned closer to bulky objects such as commodes, wheelchairs and large chairs during transfers.

Additionally its sculptured base design allows caregivers to get closer to clients during transfers, while concealing all working components.

The Oxford Presence offers versatility in its range of sling systems.

## Vega 505



**Vega 505** is a mobile patient lift adapted for safe and easy lifting of users weighing up to 230 kg. Vega 505 features a unique design with a lift arm that can be both raised to an almost upright position and lowered all the way down to the floor. It is also relatively narrow and compact, with dimensions adapted for use in premises and situations where space is limited.

In spite of the handy size, Vega505 offers an extremely large lifting range. Therefore, the lift can manage all lifting situations and requirements; both low and high lifting, seated or supine, to and from the floor, bed or chair, and gait training.

### Specifications

#### Eva 600

Safe Working Load	270kg
Material	Aluminium
Base width, outer dimensions	750-1050mm
Base width, inner dimensions	650-1050mm
Base widening	Electrical
Total weight	39kg
Front castors, diameter	35mm (Low leg) or 100mm (standard height)
Rear castors, diameter	100mm
Lifting range	500-1810mm
Lifting speed without load	35mm/sec
Emergency lowering	Manual and electrical
Battery capacity	2.9Ah
Material, sling bar	Aluminium
Sling bar width	600mm
Protection class	IPX4

#### Vega 505

Safe Working Load	230kg
Material	Powder-coated steel
Total Height	1235-1998mm
Base Length	1210mm
Base Width (Outer Dimensions)	670-1065mm
Base Width (Inner Dimensions)	550-925mm
Base Widening	Electrical
Total Weight	42.8kg
Lifting Range	230-1765mm
Lifting Speed Without Load	37mm/sec
Emergency Lowering	Manual and electrical
Battery Capacity	2.9Ah
Sling Bar Material	Aluminium
Sling Bar Width	450mm
Protection Class	IPX4



## Jasmine



**The Jasmine** Mobile Lift is a flexible solution that offers high comfort for all clients. The lift covers all needs, providing safe patient handling with up to 200kg weight capacity. With its expansive, wide opening base and high lift mechanism, Jasmine makes life easy for caregivers operating this lift system.

The control box with diagnostic system is an intelligent service monitoring system that enables a safe operating environment for the caregiver, whilst allowing maximum comfort for the client during each transfer.

It is exceptionally mobile and easy to move around. The wide opening base allows easy access for a wheelchair or armchair, whilst the high lifting mechanism is essential for helping clients on and off high toilet chairs or examination couches. Flexible and with optimized maneuverability, Jasmine covers all needs, at all times - for both the caregiver and the client.

Specifications	Jasmine
Safe Working Load	200kg
Length	1340mm
Minimum Base Width	690mm
Maximum Base Width	1050mm
Arm Height	540-1920mm
Ground clearance	120mm
Unit weight	43kg
Battery time	40 cycles

# STANDING HOISTS

## Salsa 200



**SALSA 200:** Designed as an active standing aid allowing a single carer to raise a patient into a comfortable secure standing position. The Salsa 200 is ideal for transferring from bed to chair, or chair to commode. With a small footprint and low overall weight, the Salsa 200 is highly manoeuvrable. A high capacity safe working load of 200kg means the Salsa 200 is equally at home in an institutional or home environment.



## Oxford Journey



**JOURNEY:** A mobile, folding, battery operated stand-up hoist which brings a person from sitting to a supported standing position. It has a 'cow-horn' mechanism for sling attachment which allows for a wide range of client height and sizes.

The knee pad is adjustable. Clients can be lifted from low chairs. The hoist is suitable for domestic and healthcare facility use. When folded it can stand unsupported.

Specifications	Salsa 200
Safe Working Load	200kg
Base length	1010mm
External base width closed	665mm
External base width open	1030mm
Internal base width closed	565mm
Internal base width open	930mm
Base width adjustment	Electric
Under bed clearance	130mm
Minimum height lift arm	880mm
Maximum height lift arm	1685mm
Under base height	55mm
Lifter weight	51kg
Minimum storage height	1190mm
Footplate	Removable
Kneepad	Height adjustable

	Journey
Safe Working Load	155kg
Length of base	1000mm
Height of base	110mm
Width overall of base closed	685mm
Width internal of closed base	590mm
Width internal of open base	875mm
Turning cycle	1145mm
Clearance under base to ground	30mm
Weight overall	40kg
Width of castors	75mm
Height overall	1130-1600mm
Height of spreader bar	720-1530mm

## MiniLift 125



**MINILIFT 125:** A mobile sit-to-stand lift developed for helping users, as gently as possible, to rise from a seated to a standing position. Used in combination with the right accessories, the user gets support under the feet, for knees and lower legs and behind the back. This provides for a secure and safe sit-to-stand procedure.

To be able to understand how comfortable MiniLift is compared with other sit-to-stand devices on the market, MiniLift must be tried! The movement of the lift arm is designed so that the pulling motion ends comfortably in the lower back, which prevents the sit-to-stand vest from riding up under the arms.

MiniLift provides for a natural and active sit-to-stand procedure where the user exercises both leg muscles and balance. MiniLift is made from steel, giving strength and stability.

## MiniLift 160



**MINILIFT 160:** A mobile sit-to-stand lift which has been developed to assist the user when rising from a sitting to a standing position as gently as possible. When MiniLift160 is combined with the appropriate lifting accessories, the user gets support under the feet, for the front of the lower legs and behind the back, which provides for a safe and secure, yet active sit-to-stand procedure.

### Four variants are available

MiniLift160 is available in four variants with **electrical (EE)** or **manual (EM)** base widening and with standard height or low legs for use with lower beds. All variants are manufactured in steel for stability and strength and are suitable for users weighing up to 160 kg/350 lbs.

MiniLift160 offers a unique combination of functionality, performance and quality in relation to price. A more economical solution is hard to find.

Specifications	MiniLift 125
Safe Working Load	125kg
Length of base	900mm
Width of base (Inner)	445-745mm
Width of base (Outer)	590-890mm
Height	980mm
Height of footplate	70mm
Recommended user height	1400-2000mm
Total weight	39kg
Lifting speed without load	35mm/sec
Castor size	80mm
Material	Powder-coated steel

	MiniLift 160
Safe Working Load	160kg
Base widening	Manual or electrical base widening
Recommended user height	1400-2000mm
Material	Powder-coated steel
Total weight	40.5kg
Front castors (diameter)	100mm(standard height) or 35mm(low leg height)
Rear castors (diameter)	100mm
Lifting speed without load	35mm/sec
Emergency lowering	Manual and electrical



# STANDING HOISTS

## MiniLift 200



**MINILIFT 200:** A mobile sit-to-stand lift which has been developed to, as gently as possible, assist the user when rising from a sitting to a standing position. When MiniLift200 is combined with the appropriate lifting accessories, the user gets support under the feet, for the front of the lower legs and behind the back, which provides for a safe and secure, yet active sit-to-stand procedure.

MiniLift200 is a small and convenient lifter, easy to manoeuvre. It has ergonomic and easy-to-use hand control with 4 buttons, grip-friendly handles with multiple options for hand placement.

**Other features include:** Soft, adjustable lower leg support, low foot plate with anti-slip surface, electrical emergency stop readily available on the control box.

## Roze



**ROZE:** Standup lifter, compact and manoeuvrable and provides an easy, safe and comfortable assisted transfer for patients in care or those with rehabilitation needs. Its design allows patients to be transferred or assisted from either a bed or a chair. Whether in the home, aged care facility or hospital, the Roze is the ideal stand-up lifter for the daily transferring of patients.

The Roze features an ergonomic lift angle designed to minimise shear when lifting a patient. The handles on the lifting boom enable the user to adjust their hand position, making them feel comfortable and secure during raising and lowering. The Roze lifts smoothly to a full standing position and for those who only need help rising, simply remove the footplate. The large height adjustable knee pad caters for a range of different patient heights.

The Roze can be used for two types of transfers; standing assistance or seating assistance.

Specifications	MiniLift 200
Safe Working Load	200kg
Length of base	980mm
Width of base (Inner)	470-930mm
Width of base (Outer)	580-1030mm
Height	1030mm
Height of footplate	60mm
Recommended user height	1400-2000mm
Total weight	49kg
Lifting speed without load	35mm/sec
Castor size	100mm
Material	Powder-coated steel
Emergency lowering	Manual and electric

	Roze
Safe Working Load	200kg
Base Width Open	1140mm
Base Width Closed	660mm
Base Length	1036mm
Overall Height	1247mm
Overall Length	1117mm
Overall Width	660mm
Castor Size (Front/Rear)	100mm
Total Weight	52.5kg
Hoist Range	641mm
Turning Radius	1380mm
Battery	24V DC (RCHBL)
Charger Input	100-240V AC
Charger Output/Charging Time	29.5V DC, max 6 hours
Approx Lifts Per Charge	100-200 cycles per charge

## Taurus 200



**TAURUS 200:** An aluminium stand-up stand up hoist with a Safe Working Load of 200kg; it is electric raised and lowered by Linak. Leg adjustment is controlled through the use of a foot pedal control while the rubber footplate provides a non-slip standing.

For full adjustable positioning comfortable soft polyurethane knee pads are available along with an adjustable hand bar for optional lifting. Its quick release structure enables it quicker, more compact disassembling.



Specifications	Taurus 200
Safe Working Load	200kg
Length of base	980mm
External base width	595mm
Internal base width	595-895mm
Base width adjustment	Manual
Under bed clearance	110mm
Height lift arm	89-1450mm
Minimum storage height	930mm
Machine weight	30kg

# ACCESSORIES



## Standard Yoke

2 sling attachment points at extremity of curved yoke bar  
Use with general purpose (loop attachment) slings  
Non-absorbent polyurethane padding

**Indications:** Suitable for the majority of patients  
**Useful for:** All day-to-day patient lifting



## Integrated Standard Yoke

Reduces loss of lifting height compared with other hoist scales  
Non-absorbent polyurethane cover padding



## 4 Point Yoke

4 sling attachment points spread over a broad area  
Use with general purpose (loop attachment) slings

Padded vinyl covers with velcro closure

**Indications:** Bariatric clients, clients requiring a semi-supine lift to maintain upper body control

**Useful for:** Supine lifting devices eg. Jordan frame



## Integrated Pivot Frame

Powder coated pivot frame with a SWL of 200kg  
Complete with a secure press fit self-skinning polyurethane cover  
Suitable for lifting with weight scale attachment  
Optional powered version available



## Lifting Frame

Powder coated tubular metal frame with adjustable plastic slats  
Quick release plastic clips for easy disassembly  
Suitable for lifting with weight scale attachment



## Hi-Lift Yoke



2 sling attachment points at extremity of slightly curved yoke bar  
Use with general purpose (loop attachment) slings

Padded vinyl cover with velcro closure

**Indications:** Where lifting height of specified hoist is insufficient (increases lifting height by 80mm)

**Useful for:** Reducing the loss of lifting height when installing an Allegro Universal Weighing Device

## Tri-Hook Yoke



6 slings attachment points at extremity of curved yoke bar  
Use with general purpose (loop attachment) slings

Non-absorbent polyurethane padding

**Indications:** Where the sling prescribed has more than the usual 4 attachment loops

**Useful for:** Facilities which have historically trained with this configuration

## Pivot Frame



4 sling attachment points (2 at upper extremities & 2 in lower centre of lifting cradle)

Use with pivot slings (clip or Eclip attachment)

Non-absorbent polyurethane padding

**Optional integrated weigh scale available**

**Indications:** Where patient needs to be tilted for upper body stability, where patient needs to be sat upright to facilitate good positioning

**Useful for:** Large hospitals with many staff - limited variations in sling attachment options

## Powered Pivot Frame



4 sling attachment points (2 at upper extremities & 2 in lower centre of lifting cradle)

Use with pivot slings (clip or Eclip attachment)

Non-absorbent polyurethane padding

**Optional integrated weigh scale available**

**Indications:** As per regular pivot frame but where manual tilting of the pivot frame is identified as an OH&S risk

**Useful for:** Preventing inadvertent tilting of pivot frame

## Weight Scale



Universal Weighing module with tare function and kg/lb conversion  
Suitable for yoke or pivot attachments

**Available** on all Allegro brand hoists and some non-Allegro hoist (subject to Hoist's brand)

**Useful** where weighing of patients is difficult due to the level of support required



### **Active Mobility Systems**

Unit 8, 110-120 Silverwater Rd., SILVERWATER NSW 2128

**P:** 02 9649 2111     **F:** 02 9649 8506

**W:** [www.activemobility.com.au](http://www.activemobility.com.au)     **E:** [sales@activemobility.com.au](mailto:sales@activemobility.com.au)

