

# Pathrider™ 140 XL

ENGINEERED FOR  
POWERFUL PERFORMANCE  
AND EXCEPTIONAL STYLE

## PATHRIDER™ 140 XL

Bristling with high performance features like full suspension and a hydraulic sealed brake system, the **Pathrider™ 140 XL** is a powerful blend of power and precision. The Pathrider 140 XL is equipped with sleek aggressive style and a wealth of standard luxury touches including a wraparound easy drive tiller and LED lighting, making it the ultimate outdoor scooter.



# Pathrider™ 140 XL

|                                     |                                                                                                                                                                             |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight capacity:                    | 181 kg (400 lbs.)                                                                                                                                                           |
| Maximum speed <sup>1</sup> :        | Up to 15 km/h (9.32 mph)                                                                                                                                                    |
| Ground clearance <sup>2</sup> :     | 13.33 cm (5.25") at shroud                                                                                                                                                  |
| Turning radius:                     | 210.8 cm (83") right/ 208.3 cm (82") left                                                                                                                                   |
| Overall length <sup>2</sup> :       | 142.8 cm (56.25")                                                                                                                                                           |
| Overall width <sup>2</sup> :        | 69.2 cm (27.25")                                                                                                                                                            |
| Front tyres:                        | 10 cm x 33 cm (4" x 13") pneumatic                                                                                                                                          |
| Rear tyres:                         | 10 cm x 33 cm (4" x 13") pneumatic                                                                                                                                          |
| Seat-to-deck:                       | 53 cm (21")                                                                                                                                                                 |
| Seat-to-ground:                     | 72.39 cm - 68.58 cm (28.5" - 27")                                                                                                                                           |
| Suspension:                         | Front & rear                                                                                                                                                                |
| Range per charge <sup>1,4</sup> :   | Up to 35 km (21.7 miles) (with 75 AH batteries)                                                                                                                             |
| Maximum obstacle climbing ability:  | 13 cm (5")                                                                                                                                                                  |
| Total weight without batteries:     | 117.70 kg (259.5 lbs.)                                                                                                                                                      |
| Heaviest piece when disassembled:   | Main frame: 93.21 kg (205.5 lbs.)                                                                                                                                           |
| Standard seating:                   | Type: Pillow top<br>Weight: 21.77 kg (48 lbs.)<br>Material: Black Vinyl<br>Dimensions: width - 49.5 cm (19.5") (overall width)<br>depth - 44.5 cm (17.5") (effective depth) |
| Drive system:                       | Rear-wheel drive, sealed transaxle, 24-volt DC motor                                                                                                                        |
| Dual braking system:                | Regenerative and electromechanical (hand brake)                                                                                                                             |
| Battery requirements <sup>3</sup> : | Two 12-volt, deep cycle<br>Size: 70 AH (gel)<br>Weight: <b>70 AH:</b> 25 kg (55 lbs.) each                                                                                  |
| Battery charger:                    | 8-amp, off-board                                                                                                                                                            |

Colours:



Candy Apple Red



Yellow



Silver

## Features

- Full suspension for optimum handling
- Sealed hydraulic brakes
- Large 33 cm (13") pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and headlight
- Easy drive tiller with wraparound handles
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rear view mirror standard
- Front shield standard
- Pillow-top seat

## Options

- Double crutch holder
- Oxygen tank holder
- Rear basket
- Additional rear view mirror

<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

<sup>2</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

<sup>3</sup> AGM or Gel-Cell type required.

<sup>4</sup> Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.



Active Mobility

Unit 8, 110-120 Silverwater Rd  
SILVERWATER NSW 2128  
Tel: 02 9649 2111  
E: Sales@activemobility.com.au

[www.activemobility.com.au](http://www.activemobility.com.au)

