

GO-GO[®] ENDURANCE Li

Compact, foldable seat with armrests

Delta tiller with charger port

Long-lasting lithium-ion battery

High-intensity LED headlight

Feather-touch disassembly

Interchangeable colour panels for front and back

CTS Suspension (right)

Shown in Garnet Red (matte)

**DISCOVER THE
PORTABLE POWER
OF LITHIUM ION**

140%

Faster Charging Time

60%

Lighter Weight

300%

Longer Battery Life



Feather-touch disassembly

With the **Go-Go[®] Endurance Li**, travelling has never been easier! This 4-wheel scooter has everything you need for a safe and convenient trip. With the standard 8AH airline-compliant lithium-ion battery pack and feather-touch disassembly, the Go-Go Endurance is perfect for air travel. When you arrive at your destination, enjoy a smooth, comfortable ride with Comfort-Trac Suspension.

Specifications

Model Name	Go-Go® Endurance Li
Weight Capacity	147 kg
Maximum Speed ¹	6.7 km/h
Ground Clearance ²	3.6 cm at motor
Turning Radius ²	122.5 cm
Overall Length ²	107 cm
Overall Width ²	52 cm
Seat-to-Deck Height ²	41.2 - 45 cm
Seat-to-Ground Height ²	53.9 - 57.7 cm
Front Tyres ²	5 x 20.3 cm solid
Rear Tyres ²	6.35 x 18 cm solid
Range Per Charge ^{1,3}	Up to 11.5 km (8AH)** Up to 23.1 km (16AH MAXX)
Total Weight Without Batteries ²	46.5 kg (w/o battery) 46 kg (with 8AH** battery) 51.6 kg (with 16AH MAXX)
Heaviest Piece When Disassembled ²	19 kg (front section)
Standard Seating	Type: Compact, foldable Material: Black vinyl Dimensions: 43.1 x 43.1 cm (17" x 17") 50.8 x 45.7 cm (20" x 18") Weight: 10.4 kg (43.1 x 43.1 cm) 14.1 kg (50.8 x 45.7 cm)
Motor Output	24-volt DC motor, sealed transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ²	Size: 16AH (MAXX) lithium ion pack ⁴ Weight: 3.6 kg (8AH); 5.4 kg (16AH MAXX)
Battery Charger	Off-board, 3.5 amp (lithium ion)
Warranty	Frame: Lifetime limited Electronics: 1-year limited Drive motors: 2-year limited Batteries: 2-year limited

Features

- Per charge range up to 23.1 km w/ 16AH MAXX battery pack; up to 11.5 km w/ 8AH battery pack**
- Delta tiller with ergonomic wraparound handles lets you operate the scooter with one hand and rest your wrists
- Convenient dual charging ports can charge battery pack on-board or off-board
- Includes two sets of easily changeable, coloured panels
- Two seat options: 43.1 x 43.1 cm (17" x 17") and 50.8 x 45.7 cm (20" x 18")

**Airline-compliant. Please see note on back page for details.

Available Accessories

- 8AH travel battery option available
- Underseat storage box
- Rear bag / walking stick holder
- Walker holder (*Pride® rear bag required*)
- Oxygen tank holder (*Pride® rear bag required*)
- Mobile phone holder
- Cup holder
- Saddle Bag



Note: Transport of this item on commercial aircraft is subject to federal regulations and airline policy. Please consult your airline prior to your flight to ensure your Go-Go® Endurance Li and its lithium ion battery are permitted.

Available Colours Warranty Information



Garnet Red (matte)

Euro Grey

Includes two sets of easily changeable, coloured panels!

Scooters: 12 Month Warranty for all electronic parts incl controllers & batterycharges

Scooter Frames: 24 Month warranty on the frame incl platform, fork, seat post, drivetrain, differential, motor, brakes and welds.

Scooter Batteries: 6 Month warranty

The information contained herein is correct at time of publication; we reserve the right to alter specifications without prior notice.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition, and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius, and ground clearance can be subject to variance of + or - 3%. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tyre condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Results derived from theoretical calculations based on lithium battery specifications and drive system performance. Test conducted at maximum weight capacity.
4. Does not meet airline requirements.



Quality Endorsed Company
www.qc.com.au
SAI Global

